SAFETY DATA SHEET

1. Product and Company Identification

Product identifier **Transflo MV**

Other means of identification Not available

Recommended use Lubricant

Recommended restrictions None known.

Manufacturer information Irving Blending & Packaging
PO Box 1169
Saint John, NB E2L 4E6 CA
Phone: 1.800.574.5823
Emergency Phone: 1.800.424.9300 (CHEMTREC)

Supplier See above.

2. Hazards Identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

WHMIS 2015 defined hazards Not classified

Label elements

Hazard symbol None.

Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC) None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) None known

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Not applicable.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based		72623-86-0	60-80*
Mineral Oil		Mixture	10-30*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments *CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

Inhalation If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Ingestion	Do not induce vomiting. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. IF exposed or concerned: Get medical advice. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Wear rubber gloves and safety glasses with side shields. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Firefighters should wear a self-contained breathing apparatus.
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self-contained breathing apparatus.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	May include and are not limited to: Oxides of nitrogen. Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water . Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use personal protective equipment as required. When using, do not eat, drink or smoke. Wash thoroughly after handling. Keep container tightly closed.
Conditions for safe storage, including any incompatibilities	Store in a closed container away from incompatible materials. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	1 mg/m3	Mist.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.

U.S. - OSHA

Components	Type	Value
Mineral oil (CAS Mixture)	TWA	5 mg/m3

ACGIH

Components	Type	Value
Mineral oil (CAS Mixture)	TWA	5 mg/m3

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Canada - Alberta OELs: Skin designation

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethyl acrylate (CAS 140-88-5) Can be absorbed through the skin.

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields.

Skin protection

Hand protection Rubber gloves. Confirm with a reputable supplier first.

Other Wear appropriate chemical resistant clothing. As required by employer code.

Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and Chemical Properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	Dark red
Odor	Odorless to Slight petroleum
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	-54.4 °F (-48 °C)
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	359.6 °F (182.0 °C) Pensky-Martens Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Negligible
Vapor density	Not available.
Relative density	0.8539 @ 15°C
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	7.64 cSt @ 100°C 34 cSt @ 40°C
Other information	
Percent volatile	Non-volatile

10. Stability and Reactivity

Reactivity	This product may react with oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Avoid temperatures exceeding the flash point. Do not mix with other chemicals.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of nitrogen. Oxides of carbon.

11. Toxicological Information

Routes of exposure	Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	**Species**	**Test Results**
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
		> 2000 mg/kg
		> 2000 mg/kg, 24 Hours, ECHA
Inhalation		
LC50	Rat	< 5.7 mg/L, 4 Hours, ECHA
		> 5.5 mg/L, 4 Hours, ECHA
		> 5.3 mg/L, 4 Hours, ECHA
		> 5.2 mg/L, 4 Hours, ECHA
		> 4 mg/L, 4 Hours, ECHA
		> 3.9 mg/L, 4 Hours, ECHA
		2.2 mg/L, 4 Hours, ECHA
Oral		
LD50	Rat	> 2000 mg/kg, ECHA
		5000 mg/kg, ECHA
Mineral Oil (CAS Mixture)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
LC50	Not available	
Oral		
LD50	Rat	> 5000 mg/kg

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Exposure minutes	Not available.
Erythema value	Not available.
Oedema value	Not available.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Corneal opacity value	Not available.
Iris lesion value	Not available.
Conjunctival reddening value	Not available.
Conjunctival oedema value	Not available.
Recover days	Not available.

Respiratory or skin sensitization

Canada - British Columbia OELs: Respiratory or skin sensitiser

Ethyl acrylate (CAS 140-88-5)	Capable of causing respiratory, dermal or conjunctival sensitization.
Respiratory sensitization	Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Mutagenicity Non-hazardous by WHMIS/OSHA criteria.

Carcinogenicity Contains < 3% (w/w) DMSO-extract

ACGIH Carcinogens

Ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Ethylene oxide (CAS 75-21-8)	A2 Suspected human carcinogen.
Naphthalene (CAS 91-20-3)	A3 Confirmed animal carcinogen with unknown relevance to humans.

Canada - Alberta OELs: Carcinogen category

Ethylene oxide (CAS 75-21-8)	Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

ETHYL BENZENE (CAS 100-41-4)	Confirmed animal carcinogen with unknown relevance to humans.
ETHYLENE OXIDE (CAS 75-21-8)	Suspected human carcinogen.
NAPHTHALENE (CAS 91-20-3)	Confirmed animal carcinogen with unknown relevance to humans.

Canada - Quebec OELs: Carcinogen category

Ethyl acrylate (CAS 140-88-5)	Detected carcinogenic effect in animals.
Ethylene oxide (CAS 75-21-8)	Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethyl acrylate (CAS 140-88-5)	Volume 39, Supplement 7, Volume 71 - 2B Possibly carcinogenic to humans.
Ethylbenzene (CAS 100-41-4)	Volume 77 - 2B Possibly carcinogenic to humans.
Ethylene oxide (CAS 75-21-8)	Volume 97, Volume 100F 1 Carcinogenic to humans.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.
Naphthalene (CAS 91-20-3)	Volume 82 - 2B Possibly carcinogenic to humans.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethyl acrylate (CAS 140-88-5)
Ethylbenzene (CAS 100-41-4)
Ethylene oxide (CAS 75-21-8)
Naphthalene (CAS 91-20-3)

US NTP Report on Carcinogens: Anticipated carcinogen

Naphthalene (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.

US NTP Report on Carcinogens: Known carcinogen

Ethylene oxide (CAS 75-21-8)	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Ethylene oxide (CAS 75-21-8)	Cancer

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Teratogenicity Not applicable.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological Information

Ecotoxicity See below

Ecotoxicological data

Components		Species	Test Results
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)			
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

Ethylene oxide (CAS 75-21-8)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

Canada DSL Challenge Substances: Listed substance

Ethyl acrylate (CAS 140-88-5)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	1 TONNES

Canada Priority Substances List (Second List): Listed substance

Ethylene oxide (CAS 75-21-8)	Listed.

Export Control List (CEPA 1999, Schedule 3)

Ethylene oxide (CAS 75-21-8)	Substance subject to notification or consent.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulations This product is NOT known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethyl acrylate (CAS 140-88-5)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Ethylene oxide (CAS 75-21-8)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable quantity

Ethylene oxide (CAS 75-21-8)	10 LBS

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Ethylene oxide (CAS 75-21-8)	Cancer Reproductive toxicity Mutagenicity Central nervous system Skin sensitization Skin irritation

Eye irritation
respiratory tract irritation
Acute toxicity
Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
SARA 302 Extremely hazardous substance	No
SARA 311/312 Hazardous chemical	No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethyl acrylate (CAS 140-88-5)
Ethylbenzene (CAS 100-41-4)
Ethylene oxide (CAS 75-21-8)
Naphthalene (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ethylene oxide (CAS 75-21-8)

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	Listed.
Ethyl acrylate (CAS 140-88-5)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Ethylene oxide (CAS 75-21-8)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

US - Illinois Chemical Safety Act: Listed substance

Ethyl acrylate (CAS 140-88-5)
Ethylbenzene (CAS 100-41-4)
Ethylene oxide (CAS 75-21-8)
Naphthalene (CAS 91-20-3)

US - Louisiana Spill Reporting: Listed substance

Ethyl acrylate (CAS 140-88-5)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Ethylene oxide (CAS 75-21-8)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

US - Minnesota Haz Subs: Listed substance

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	Listed.
Ethyl acrylate (CAS 140-88-5)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Ethylene oxide (CAS 75-21-8)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

US - New Jersey RTK - Substances: Listed substance

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)
Ethyl acrylate (CAS 140-88-5)
Ethylbenzene (CAS 100-41-4)
Ethylene oxide (CAS 75-21-8)
Naphthalene (CAS 91-20-3)

US - North Carolina Toxic Air Pollutants: Listed substance

Ethylene oxide (CAS 75-21-8)

US - Pennsylvania RTK - Hazardous Substances: Special hazard

Ethyl acrylate (CAS 140-88-5)
Ethylene oxide (CAS 75-21-8)

US - Texas Effects Screening Levels: Listed substance

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	Listed.
Ethyl acrylate (CAS 140-88-5)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Ethylene oxide (CAS 75-21-8)	Listed.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	Listed.

Naphthalene (CAS 91-20-3) Listed.

US - Washington Chemical of High Concern to Children: Listed substance

Ethylbenzene (CAS 100-41-4)

US. Massachusetts RTK - Substance List

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)
Ethyl acrylate (CAS 140-88-5)
Ethylbenzene (CAS 100-41-4)
Ethylene oxide (CAS 75-21-8)
Naphthalene (CAS 91-20-3)

US. New Jersey Worker and Community Right-to-Know Act

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)
Ethyl acrylate (CAS 140-88-5)
Ethylbenzene (CAS 100-41-4)
Ethylene oxide (CAS 75-21-8)
Naphthalene (CAS 91-20-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)
Ethyl acrylate (CAS 140-88-5)
Ethylbenzene (CAS 100-41-4)
Ethylene oxide (CAS 75-21-8)
Naphthalene (CAS 91-20-3)

US. Rhode Island RTK

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)
Ethyl acrylate (CAS 140-88-5)
Ethylbenzene (CAS 100-41-4)
Ethylene oxide (CAS 75-21-8)
Naphthalene (CAS 91-20-3)

US. California Proposition 65

WARNING: This product can expose you to chemicals including Ethyl acrylate, which is known to the State of California to cause cancer, and Ethylene oxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethyl acrylate (CAS 140-88-5)	Listed: July 1, 1989
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
Ethylene oxide (CAS 75-21-8)	Listed: July 1, 1987
Naphthalene (CAS 91-20-3)	Listed: April 19, 2002

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8)	Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene oxide (CAS 75-21-8)	Listed: August 7, 2009

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer	The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.
Issue date	06-August-2019
Version #	03
Effective date	06-August-2019
Prepared by	Dell Tech Laboratories Ltd. Phone: (519) 858-5021
Other information	For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.